

KIT POE IP de 4 Cámaras



4 PCS Network Camera kit

Features :

- Camera Details:
 - 720P Network Camera
 - 24 pcs IR LEDs,3.6 mm lens
 - Indoor & outdoor use
- NVR Details:
 - 4CH 720P Resolution
 - with 4 CH POE Function (offer 15V power)
 - Support Max.1 Sata HDD (Max.4TB)
 - Support VGA /HDMI output
 - Support External WIFI /3G USB Module

Technology data

IP Camera	4	<p>DIY Wired POE Network Surveillance System</p> <p>1. NVR offer power to Camera via UTP cable , no need external power for cameras</p> <p>2. Camera connect to NVR automatically, no need other setting in NVR menu</p> <p>3. Support Mobile Surveillance via P2P</p> <p>4. 720p resolution ip camera, 24 pcs IR LEDs, 3.6mm lens</p>
POE NVR	1	
15V/5A Power adapter	1	
CD Disk	1	
USB mouse	1	
1.5 M UTP Cable	1	
20 M UTP Cable	4	
Screws	1 SETS	
User manual	1	

Style	Feature	720P POE NVR kit
IPC specification		
System	System source	Embedded LINUX OS HI3518
Sensor	Sensor	1.0 Mega Pixel, 1/4" Progressive scanning CMOS
	Illumination	Color :0.1 Lux@F1.2,B/W:0 Lux@F1.2(IR ON) 100W
	Lens	3.6mm mega fixed lens
Others	Video compression	H.264 High profile
	Video code rate	1Mbps~6Mbps
	Resolution	Main code stream:1280*720,704*576; Sub code stream:704*576,352*288
Standard	Waterproof level	IP67
	IR distance	10-25 meters
	Power supply mode	NVR POE
	Communication mod	P2P
	Dimension	107 mm (L) * 68 mm (W) * 60mm (H)
NVR specification:		
System	System source	Embedded LINUX OS HI3515
	System source	Simultaneously multirecord/playback/users/back-up
Interface	OS	16bit real color imaging OS menu, supporting mouse
	Image display	1/4 picture
Video	Input	4CH 720P(1280*720)
	playback	960P/720P
	monitor	VGA: HD; HDMI: HD
	Motion detection	Support
Video playback	Record mode	Manual/dynamic detection/timing
	Local playback	1CH playback
	Record query	Timing/Calendar/Event/Channel query
Storage back-up	Record storage	HDD/network
	Back-up mode	Network back-up/USB mobile hard disk

Standard	Video output	1pc VGA,1 pc HDMI 1 pc BNC,1 pc VGA
	Network interface	5pcs RJ45,10M/100M self
	USB interface	2pcs USB interface
	HDD interface	1pc SATA interface (MAX 4T)
	Power supply	DC15V/5A
	Dimension	White: 235(L)*205(W)*45(H)mm

Application range:

No need wiring, play & plug, wide used in family and shop



